
















<p>Staple - Extrusion MF 24' 6063T5</p>	 <p>14000 Size: 1 X 1 X .093 Wt. Lin. Ft. .398</p>	 <p>14005 Size: 1 X 1 X .100 Wt. Lin. Ft. .442</p>	 <p>14010 Size: 1 X 2 X .093 Wt. Lin. Ft. .603</p>
 <p>14015 Size: 2 X 1 X .093 Wt. Lin. Ft. .691</p>	 <p>14016 Size: 2 X 1 X .043 Wt. Lin. Ft. .484</p>	 <p>14018 Size: 2 X 2 X .125 Wt. Lin. Ft. 1.158</p>	 <p>14020 Size: 4 X 1 X .043 Wt. Lin. Ft. 1.158</p>
 <p>14052 90° Awning Rail Size: 24' Wt. Lin. Ft. .076</p>	 <p>14055 Female Awning Size: 27' Wt. Lin. Ft. .385</p>	 <p>14056 Male Awning Hinge Size: 27' Wt. Lin. Ft. .270</p>	 <p>14065 2" Bahama Blade Size: 18' Wt. Lin. Ft. .281</p>
 <p>19997 L2 Louver Blade Size: 20' Wt. Lin. Ft. .406</p>	 <p>19998 2 x 3/4 Channel Size: 24' Wt. Lin. Ft. .439</p>		